



# HOW TO

## Replace a toilet seat



### CONTACT US

#### HEAD OFFICE:

230 15th Avenue, Riviera, Pretoria  
Tel: +27 12 356 9500

#### STORES:

Centurion Megastore: +27 12 653 9600, Montana Megastore: +27 12 523 0400,  
Randburg: +27 11 699 7560, Riviera: +27 12 356 9500, Silver Lakes Megastore: +27 12 809 9900,  
Waltloo: +27 12 803 5158, Waterkloof Glen: +27 12 998 5074

[www.chamberlain.co.za](http://www.chamberlain.co.za)



**FAMOUS FOR HARDWARE** since 1903

**FAMOUS FOR HARDWARE** since 1903

\* Please note: Information in this brochure is FH Chamberlain's opinion and we do not warrant the accuracy or completeness of that information.  
FH Chamberlain excludes all liability in relation to the statements in this booklet.

Replacing a toilet seat is a straightforward do-it-yourself job – no plumber needed. So, when your toilet seat gets damaged – oftentimes easily – it’s a quick fix that requires a couple of tools and a bit of time. What’s great, there’s no need to turn off the water mains. Toilet seats are available in a multitude of styles, and two general sizes: round and oblong/elongated.

## INSTALLATION GUIDE



1 Locate the mounting bolts and nuts at the hinge of the toilet seat.



2 Next, place a screwdriver on one of the mounting bolt heads. Firmly holding the corresponding nut (underneath the toilet base), turn the screwdriver anti-clockwise to loosen.

**Warning:** Most anchor bolts and nuts are made of plastic, so, take care when applying force.

### What you will need:

- Tape measure
- Screwdriver
- Adjustable wrench
- New toilet seat

### Chamberlains DIY tip!

Be sure to measure the old seat before purchasing a replacement one.



3 Remove both sets of mounting bolts and nuts.



4 Lift off the old seat. Clean the toilet base before installing the new seat.



5 Align the holes of the new seat with those of the toilet’s base. Push the mounting bolts through the holes. Screw on the nuts from underneath until hand-tight.

### Chamberlains DIY tip!

Don’t over-tighten the nuts. It’ll be harder to remove them at a later stage.



**Steven de Beer**  
Plumbing expert, Centurion  
26 years at Chamberlains